

Space Saver Smart S8



Space Saver Smart S8

MODEL Space Saver Smart S8

FEATURE

- » 8 tools ATC armless
- » 1.5 HP spindle motor
- » BT30 spindle taper
- » 8,000 rpm spindle speed
- » 3 axes linear guide way

Click to enlarge this image
 Request a quote
 See our accessory
 Tell a friend

SIMILAR PRODUCTS
 SPECIFICATION
 E-CATALOG

- Centroid M400i control with 15" LCD
- 8 tools ATC armless
- 1.5HP spindle motor, BT30 spindle taper
- 8,000 rpm spindle speed
- 3 axes linear guide way
- Precision ball screws for high accuracy and long lasting
- FC30 Meehanite casting main frame with annealed & stress relieved for long term reliability
- 100% laser tested for positioning accuracy & repeatability
- Telescopic steel way covers on all three axes
- Tool box & tools
- Coolant system and air blast system
- Central lubrication system
- Rigid tapping (opt)
- Portable hand wheel (opt)

Specification	
Table	32" x 9.45"
Longitudinal travel (X-axis)	15.37"
Cross travel (Y-axis)	9.45"
Vertical travel (Z axis)	13.75"
Spindle nose to table top (D)	1.18" to 14.95"
Spindle taper & pull force	BT30 & 300 Kg
Spindle speed	8000 rpm
Load capacity	220 lbs
Transmission of spindle & motor	Belts
Spindle center to column front surface	10
Feed Rate	
Rapid feed rate	X/Y: 300ipm Z: 300 ipm

Cutting feed rate	1 - 100 ipm
Motor	
Spindle motor/max torque	1.55 HP
Servo motors on XYZ	0.75 kW
Coolant pump	1/8 HP
Lubrication pump	150 W
Power requirement	10 KVA, 3 Phase 208V to 230V (Max)
Automatic Tool Changer	
No. of tools	8
Max tool diameter	2"
Max tool weight	10 lbs
Dimension & Weight	
Length x width x height	74" x 48" x 79"
Net weight	2640 lbs

Standard Accessories		
Tools & box	Leveling bolts & plate	RS-232 interface
Operation manual	Full enclosure	Air blast, coolant flush gun
Auto lube system	Coolant system	60 GB solid state hard drive
Halogen work light	USB 2.0 port	Shop floor programming/Conversational